

Thawing Baths


CB 704

CB 705

REMI Thawing bath offer quick and optimum thawing of plasma at required temperature levels.

Available in two variants Refrigerated & Non-Refrigerated

CB 704, is a refrigerated thawing bath for preparation of cryoprecipitate at required temperature of 4°C

CB-705, is a non-refrigerated thawing bath for quick thawing of plasma at required temperature of 37°C

Salient Features

- Microprocessor based precise temperature control
- High performance 1.5 kw heater & compressor to achieve the set temp
- Over temperature safety limit, audio visual alarm
- LED monitor to display the working status of thawing bath
- Continuous water circulation for temp uniformity & rapid thawing
- Audio visual alarm after elapsed time

Technical Specifications

Particulars	CB-704	CB-705
Temperature settings	+ 4°C & + 37°C (accuracy ± 1°C)	+ 37°C (accuracy ± 1°C)
External Dimensions W x D x H (mm)	910 x 600 x 1090	760 x 530 x 640
Thawing Timer	Adjustable up to 2 Hrs	
Internal Body Material	Stainless Steel AISI304 Grade	
External Body Material	Powder Coated CRCA Steel	
Noise Level	Less Than 65 db(A)	
Recommended Line Voltage Corrector	3 KVA	
Electrical	220-240 volts, 50 Hz, SINGLE PHASE	

Specifications subject to change without notice

V. S. International Pvt. Ltd.

A-204, Neelam Centre, Hind Cycle Road, Worli, Mumbai - 400 030., INDIA.
 Contact : +91 22 4333 3900 / 2498 8777 Fax: +91 22 6660 8779